

1-20. (CANCELED)

21. (CURRENTLY AMENDED) A baffle secured to a glass-lined internal wall of a container capable of being equipped with a system of circulation of coolant, the baffle being secured to and held at a distance from ~~[[the]]~~ an adjacent internal wall (12) of the container ~~or tank~~ (1) and relative to the adjacent internal wall (12) and locally with ~~[[this]]~~ the adjacent internal wall (12) by at least one local connection (15) whose greatest dimension is ~~lower~~ less than ~~[[the]]~~ a length of the baffle, and an external surface of the baffle and an external surface of the local connection ~~[[is]]~~ are both glass-lined ~~upon the glass-lining process and after being secured to the internal wall (12), forming a group of glass-lined surfaces with an internal lateral surface of the container, and the local connection (15) enables the baffle to be~~ substantially insensitive to expansion of a remainder of the container.

22. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein the baffle is a solid body.

23. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein the baffle is a hollow body.

24. (PREVIOUSLY PRESENTED) The baffle according to claim 23, wherein a hollow interior space (16) of the baffle (14) has a connecting fluid path, via the local connection (15), with fluid of a heating or cooling system of the container for circulation of fluid.

25. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein the local connection (15) is essentially located at a vertical middle of the baffle (14).

26. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein the local connection (15) is located near a lower edge of the baffle (14).

27. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein a body of the baffle exhibits a generally flat form similar to a board, mainly vertical and perpendicular to the internal wall (12) of the container (1), with rounded edges and angles.

28. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein a body of the baffle takes the general shape of a "hockey stick".

29 (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein a body of the baffle is curved, at one or more of a vertically higher or lower part and on a side edge.

30. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein the form of a cross section of a body of the baffle is mainly rectangular and has rounded edges.

31. (CANCELED)

32. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein a body of the baffle exhibits one of concave or convex sides.

33. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein the form of a section presents at least an undulation on one of the sides of the baffle.

34. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein a body of the baffle is secured to the internal wall in an appreciably tilted presentation compared to a longitudinal axis of the container.

35. (PREVIOUSLY PRESENTED) The baffle according to claim 21, wherein the baffle is secured in skew relative to the internal wall (12) of the container (1).

36. (PREVIOUSLY PRESENTED) The baffle according to claim 35, wherein an end of a body of the baffle is close to the adjacent internal wall and in that its opposite end is further away from the adjacent internal wall.

37. (CURRENTLY AMENDED) A container intended to be glass-lined, the container comprising a baffle secured to a glass-lined internal wall of ~~[[a]]~~ the container, which is capable of being equipped with a coolant circulation system ~~of circulation of coolant~~, the baffle being secured to and held at a distance from ~~[[the]]~~ an adjacent internal wall (12) of the container ~~or tank~~ (1) and relative to the adjacent internal wall (12) and locally with ~~[[this]]~~ the adjacent internal wall (12) by at least one local connection (15) whose greatest dimension is ~~[[lower]]~~ less than ~~[[the]]~~ a length of the baffle, an external surface of the baffle and an external surface of the local

connection ~~[[is]]~~ are glass-lined, the external surface of the local connection being glass-lined during a ~~upon the glass-lining process and after being~~ after the local connection is secured to the internal wall (12), and the external surface of the baffle, the external surface of the local connection and the internal surface of the container form an assembled group of glass-lined parts which are assembled together with one another.

✓
✓
✓
✓
✓
✓

38. (PREVIOUSLY PRESENTED) The container according to claim 37, wherein the container includes several baffles (14) distributed regularly.

39. (PREVIOUSLY PRESENTED) The container according to the claim 37, wherein the container includes several baffles (14) laid out appreciably along a theoretical curve relative to the internal wall (12) of the container (1).

40. (PREVIOUSLY PRESENTED) The container according to claim 39, wherein the theoretical curve is a helix.

41. (NEW) A reaction container comprising:

an inner wall facing an interior of the container;

a plurality of baffles, each baffle having at least one local connection extending therefrom, the at least one connection being welded to the inner wall of the container to couple the baffle and the inner wall such that the baffle extends adjacent to and is spaced from the inner wall of the container and the baffle is substantially insensitive to expansion of a remainder of the container; and

the inner wall, the baffles and the local connections are glass-lined;

and

the inner wall and the local connections are glass-lined after being welded with one another such that the inner wall and the local connections have a common uniform glass-lining.